

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)



PCT/GB00/02127

| | |
|-------------------|-----|
| REC'D 13 JUL 2000 | |
| WFO | PCT |

INVESTOR IN PEOPLE

GB00/2127

4

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed *AmBrewster*

Dated 20 June 2000




Patents Act 1977
(Rule 16)

The
Patent
Office

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



07JUN99 E452387-1 D02823
P01/7700 0.00 - 501003033
Cardiff Road
Newport
Gwent NP9 1RH

The Patent Office

1. Your reference NJH/MP5778501

2. Patent application number
(The Patent Office will fill in this part)

9913058.5

04 JUN 1999

3. Full name, address and postcode of the or of each applicant (underline all surnames)

TECHNOLOG LIMITED
RAVENSTOR ROAD
WIRKSWORTH
MATLOCK
DERBYSHIRE
DE4 4FY

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UK

5805304002
J

4. Title of the invention PILOT VALVE

5. Name of your agent (if you have one)

MEWBURN ELLIS

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

YORK HOUSE
23 KINGSWAY
LONDON
WC2B 6HP

Patents ADP number (if you know it)

109006

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 11

Claim(s) 0

Abstract 0

Drawing(s) 5

10. If you are also filing any of the following, state how many against each item

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents Form 9/77) 0

Request for substantive examination (Patents Form 10/77) 0

Any other documents 0
(Please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Jonathan Linn

3 June 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

~~G. JONATHAN LINN~~
NIGEL J. HACKNEY

0161 834 0201

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

PILOT VALVE

The present invention relates to a pilot valve, for example of the type which is commonly used to control a pressure reducing valve in water and gas supply systems.

Figure 1 illustrates the use of a "single chamber" pilot valve 1 to control a pressure reducing valve (PRV - shown schematically as item 2) as commonly used in a water supply system. In the context of a gas supply system such a pressure reducing valve is normally known as a "regulator" or "governor", but herein the single term "PRV" is used for simplicity as referring to both types of system. The fluid to be controlled (usually water or gas, and in this example will be taken to be water) flows along the main pipe 3 through the PRV. The outlet pressure (P_o) is usually less than the inlet pressure (P_i) due to the action of the PRV.

The amount of pressure reduction is controlled by operation of the PRV under control of pilot valve 1. An auxiliary flow pipe 4 carries water from the inlet of the PRV to the control chamber 5 of the pilot valve 1 and then back to the outlet of the PRV. Prior to entering the control chamber 5, the water passes through a venturi chamber (or primary orifice) 6 or, more correctly in the context of a gas supply system, an inspirator 6 and the

water pressure (P_v) at the outlet side 7 of the chamber or inspirator controls the PRV.

The flow of water through the control chamber 5 is controlled by a gate mechanism 8 which is linked to a diaphragm 9. A spring 10 applies force to the rear of the diaphragm 9 and the amount of force supplied by the spring may be varied by an adjustment screw 11.

10 In a steady state situation (where P_o remains constant) the water pressure in the control chamber 5 will be balanced by the force generated the spring and the gate 8 will remain in a constant position. Thus the flow through the auxiliary pipe 4 will remain constant and P_v will remain constant.

If the control pressure (P_o) falls, the spring 10 causes the gate 8 to open further and the flow through the auxiliary pipe increases. Accordingly, the flow through the venturi 6 also increases which results in pressure P_v decreasing, causing the PRV to open further. This results in the control pressure P_o rising again and the system should then reach a steady state again at the previously set value of P_o .

25

In order to provide an improved control system, the present applicant has already disclosed a system which

uses a "dual chamber" pilot valve in European Patent No. 574241. Figure 2 shows an example of a system utilising a "sandwich plate" dual chamber pilot 20. The pilot valve 20 performs the same general function in the control system as the pilot valve of Figure 1 but in this example the adjustment previously provided by adjustment screw 11 is effectively supplemented by an adjustment using a control pressure (P_c). As further relevant background art may be mentioned the gas supply pressure control apparatus as disclosed by the present applicant in GB-A-2252848.

The pilot valve 20 includes a second chamber 21 which is effectively divided into two portions 22 and 23 by a wall 24. The control pressure P_c effectively acts against the force of spring 10 by virtue of diaphragm 26. As with Figure 1, the spring is mechanically connected by arm 28 to a gate mechanism 8 which performs the same function as previously. The arm 28 passes through wall 24 and the aperture through which it passes is sealed by a seal 29 so that chamber 23 does not contain any water but instead is vented to the atmosphere.

If the control pressure P_c remains constant, then the system operates as explained with reference to Figure 1. However, if the control pressure P_c is reduced then the gate 27 will open further thereby reducing pressure P_v and increasing the outlet pressure P_o . This is usually

referred to as a "failsafe" system since in the event that the control pressure fails i.e. falls to zero, the outlet pressure P_o will be set to its maximum value.

5 Figure 3 illustrates an alternative but mechanically equivalent "dual chamber" pilot valve arrangement to that shown in Figure 2. The arrangement of Figure 3 is sometimes referred to as a "pancake adapted" pilot. In this arrangement, the second chamber 31 is located at the
10 base of the pilot 30. As with the arrangement of Figure 2, the second chamber 31 is divided by a diaphragm 34 into two chambers 32 and 33 and the control pressure P_c is applied to chamber 32. The diaphragm 34 is mechanically linked via an arm 35 to the gate mechanism 8 but is not
15 rigidly limited to the gate or spring. The arm 35 presses into control chamber 5 via an aperture which is again sealed with seal 36.

In the embodiment of Figure 3, the control pressure
20 P_c again opposes the force produced by the spring 10 and so the control system effectively operates in an identical manner. In other words, if control pressure P_c is reduced then the outlet pressure P_o is increased.

25 One advantage over the Figure 3 arrangement as opposed to the Figure 2 arrangement is that the additional chamber 31 can effectively be retrofitted to a single

chamber pilot valve. However one disadvantage with the dual chamber pilot valves of Figures 2 and 3 is that in both cases a seal needs to be provided in order that the control fluid is prevented from entering the second part of the additional chamber i.e. that part of the chamber to which the control pressure is not applied. The provision of such a seal can be difficult and deterioration or failure of the seal may lead to reduction in performance of the pilot valve or leakage therefrom. Furthermore, the friction caused by the seal can in turn create a frictional error in the quality of the pilot valve control.

Figure 4 shows a further "hydraulic" dual chamber pilot valve arrangement. As with the previous embodiments, a second chamber 40 is provided which is divided by a diaphragm 41 into two parts 42 and 43. The control pressure P_c is applied to part 42 of the second chamber 40 and part 43 is connected to the spring chamber which is vented to the atmosphere. As before, the diaphragm 41 is mechanically connected to the gate 8, in this case via the spring 10.

However, unlike the embodiments of Figure 2 and Figure 3 in the embodiment of Figure 4 the control pressure P_c acts in the same direction as the force of the spring 10, rather than against it. This means that the

control system works in the opposite way to that of Figures 2 and 3 i.e. if the control pressure P_c is reduced then the gate 8 closes further, the venturi pressure P_v increases causing the PRV to close further and the outlet pressure to drop. This arrangement is not considered to be "failsafe" since a loss of control pressure P_c would result in the lowest possible outlet pressure P_o . This is sometimes referred to as a "direct acting" control system rather than the "reverse acting" control systems of Figures 2 and 3.

The present invention aims to provide a pilot valve of the "reverse acting" type but which eliminates the need for a seal.

In a first aspect, the present invention provides a pilot valve which includes

biassing means to control a gate for controlling fluid flow through a control chamber;

a second chamber sealed by a second chamber diaphragm into which control pressure is applicable for also controlling the operation of the gate, whereby in use an increase in control pressure acts to reduce fluid flow through the gate;

wherein the side of the diaphragm against which the control pressure is not applied is in fluid communication with the control chamber.

In this way, a "reverse acting" dual chamber pilot valve is provided in which the need for any seal in association with the second chamber is avoided.

5 The fluid which in use flows through the control chamber may or may not be the same fluid or type of fluid as the fluid which in use is used to apply the control pressure. The fluids in question may, for example, be water or gas. In other words, in one example both fluids
10 in question may be water; in another example both fluids may be gas; in a third example one fluid may be water and the other gas.

Preferably, the biasing means is a spring means or
15 spring such as a helical spring. Preferably the biasing means is biased to open the gate and may be rigidly connected to the gate by a suitable mechanical linkage. Preferably the diaphragm is also rigidly connected to the gate and/or spring via the same or a second suitable
20 mechanical linkage.

Preferably, the control chamber is at least partly bounded by a control chamber diaphragm in addition to the second chamber diaphragm. Preferably biasing means is
25 located on the opposite side of the control chamber diaphragm to the control chamber. As will be explained in detail later in the specification, by appropriately

selecting the areas of the second chamber diaphragm and the control chamber diaphragm, the effect of the control pressure on the fluid flow through the control chamber (and therefore in use, on the outlet pressure) can be
5 selected.

In a preferred embodiment, the ratio of the area of the control chamber diaphragm to the second chamber diaphragm is 2:1 or less. For example, if the control
10 chamber diaphragm is twice the area of the second chamber diaphragm then a particular drop in control pressure will result in an identical increase in outlet pressure. In a different example, if the area of the second chamber diaphragm is three-quarters that of the control chamber
15 diaphragm then an increase in control pressure of a given amount would cause the outlet pressure to decrease by three times that amount. The particular case in which the second chamber diaphragm area is half that of the control chamber diaphragm effectively replicates the function of
20 the "sandwich" and "pancake" arrangements described earlier with reference to Figures 2 and 3.

Embodiments of the present invention will now be described by way of example with reference to the
25 accompanying drawings in which:

Figure 1 is a schematic diagram of a single chamber

pilot valve control arrangement;

Figure 2 is a schematic diagram of a "sandwich" dual chamber pilot valve arrangement;

Figure 3 is a schematic diagram of a "pancake" dual
5 chamber pilot valve arrangement;

Figure 4 is a schematic diagram of a "hydraulic" dual chamber pilot valve arrangement; and

Figure 5 is a schematic diagram of a pilot valve according to an embodiment of the present invention.

10

Figure 5 shows a pilot valve 50 which includes a control chamber 51 and a second chamber 52. A control pressure P_c is applied to chamber 52 in use and chamber 52 is divided from control chamber 51 by a second chamber
15 diaphragm 53.

The second chamber diaphragm 53 is rigidly connected via linkage 54 to a gate mechanism 55. The gate mechanism 55 is also connected via a further rigid linkage 56 to a
20 spring 57. The spring 57 is isolated from the control chamber 51 by the control chamber diaphragm 58. The action of the force of the spring 57 on the diaphragm 58 may be adjusted by adjustment screw 59.

25 As can be seen from Figure 5, the control fluid (which may be gas or water) present in the control chamber 51 acts against the opposite side of the second chamber

diaphragm 53 to the control pressure P_c . In operation, if, for example, control pressure P_c is reduced then the gate 55 will open further causing the fluid flow through the control chamber to increase. When used in a PRV control circuit, as explained previously, this will cause the outlet pressure to increase.

As indicated in Figure 5, the area of the control chamber diaphragm 58 is designated A and the area of the second chamber diaphragm 53 is designated as A' . The balance of forces operating in the pilot valve is as follows:

$$\begin{aligned} SF &= A P_o - A' P_o + A' P_c \\ &= (A - A') P_o + A' P_c \end{aligned}$$

In a first example, if $A' = \frac{1}{2}A$

$$SF = A' (P_o + P_c)$$

If a "multiplication" effect is required then the relative cross-section areas can be set to a different value. In a second example, if $A' = \frac{3}{4}A$, the equation will be

$$SF = \frac{1}{4}A (P_o + 3P_c)$$

Therefore an increase of P_c of a given amount would

cause Po to decrease by three times the amount and vice versa.

The above embodiment is given by way of example only
5 and variations will be apparent to those skilled in the art.

THIS PAGE BLANK (USPTO)






FIG 1

THIS PAGE BLANK (USPTO)



F162

THIS PAGE BLANK (USPTO)

FIG 3

THIS PAGE BLANK (USPTO)




FIG 4

THIS PAGE BLANK (USPTO)

sls




FIG 5

PCT/GB001021

Newburn Ellis

2/6/00

THIS PAGE BLANK (USPTO)